

AGUAPLAST RAPID FASSADE

Ref. 13000007462/

Rev. no. 1.3

Revision Date 18.01.2023 Print Date 18.01.2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name AGUAPLAST RAPID FASSADE

Unique Formula Identifier

(UFI)

X8D1-E0JK-7008-F2F0

1.2 Relevant identified uses of the substance or mixture and uses advised

against

Powder coating

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

Beissier S.A.U. Txirrita Maleo, 14

20 100 Errentería (Guipúzcoa) Phone: +34 943 344 070 Fax: +34 943 517 802

E-mail address of person responsible for the SDS

European Union

beissier.laboratorio@beissier.es

1.4 Emergency telephone number European Union

Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

AGUAPLAST RAPID FASSADE

Serious eye damage, Category H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Precautionary statements : P102 Keep out of reach of children.

Prevention:

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P315 Get immediate medical advice/ attention.

P302 + P352 IF ON SKIN: Wash with plenty of soap and

water.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

portland cement

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Mortar/render has an alkaline reaction with water. Therefore protect your skin and eyes. Wash thoroughly with water in case of skin contact. Immediately consult a doctor in case of contact with eyes!

Risk of infection of the lung after prolonged inhalation of dust particles.

The mixture is low in chromate and may contain additives of chromate reducers, which lower the content of sensitising chromium(VI) to below 2 ppm in the cement portion of the ready-to-use mortar. A prerequisite for the effectiveness of chromate reduction is proper storage and observance of the expiry date.

AGUAPLAST RAPID FASSADE

When exceeding the shelf life of the product there is a risk of skin rash in cases of hypersensivity to Chromium (VI).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration	
	EC-No.		(% w/w)	
	Index-No.			
	Registration number			
portland cement	65997-15-1	Eye Dam. 1; H318	≥1-<3	
	266-043-4	STOT SE 3; H335		
		Skin Irrit. 2; H315		
		Skin Sens. 1B; H317		
Substances with a workplace exposure limit :				
Quartz (particle of sand < 12 µm less	14808-60-7		≥ 10 - < 20	
than 1 %)	238-878-4			

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice When symptoms persist or in all cases of doubt seek medical

advice.

Inhalation Move to fresh air.

If symptoms persist, call a physician.

Skin contact Take off contaminated clothing and shoes immediately.

Wash off immediately with soap and plenty of water.

If symptoms persist, call a physician.

Wash clothing before reuse.

Eye contact In case of eye contact, remove contact lens and rinse immediately

with plenty of water, also under the eyelids, for at least 15

minutes.

If possible, use isotonic eye rinse solution (e.g. 0,9% NaCl).

Do not rub affected area.

Call a physician immediately.

Ingestion Rinse mouth.

If conscious, drink plenty of water.

Do NOT induce vomiting.

Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Skin contact may provoke the following symptoms:

May cause skin irritation and/or dermatitis.

Causes serious eye damage.

Inhalation may provoke the following symptoms:

Cough

May cause respiratory irritation.

AGUAPLAST RAPID FASSADE

Treatment Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing

media

The product is not flammable.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

Not applicable

5.2 Special hazards arising from the

substance or mixture

5.3 Advice for firefighters

The product is neither explosive nor combustible and is also not

oxidising in relation to other materials.

No special measures required.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental

precautions

Avoid dust formation.

Use respiratory protective device against the effects of dust.

The product should not be allowed to enter drains, water courses

or the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and

cleaning up

Use mechanical handling equipment.

Moisten and remove.

Avoid whirling up dust - vacuum-clean rooms instead of sweeping.

Do not use compressed air for cleaning purposes.

Dispose of contaminated material as waste according to item 13.

Clean contaminated surface thoroughly.

6.4 Reference to other

sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling

Avoid dust formation.

When handling sacked goods and using open mixing containers. first pour in water, then carefully allow the dry mortar to run in.

Keep fall height low. Start up mixer slowly.

Do not compress empty sacks, e.g. in a larger sack.

Large loads of over 25 kg should be moved not by hand but with the aid of mechanical equipment only. Depending on the employee's age, gender and constitution and the frequency with which loads are lifted and carried, they may also induce a high

level of strain at lower weights.

Do not kneel in fresh product while working.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not re-use empty containers.

AGUAPLAST RAPID FASSADE

Hygiene measures When using do not eat, drink or smoke.

Wash hands before breaks and at the end of workday.

Avoid contact with the skin and the eyes.

Remove and wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Advice on protection against fire and explosion

against fire and explosion

Further information on storage conditions

Store in original container. Keep in a dry place.

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide,

fumes.

Protect from humidity and water.

Manufacturer's notes on storage conditions and product life must

be observed.

Advice on common storage No materials to be especially mentioned.

7.3 Specific end use(s) For further information, see also Technical Data Sheet for the

product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limit(s)

Components		CAS-No.
Basis	Туре:	Control parameters
Quartz (particle of sand	< 12 µm less than 1 %)	14808-60-7
2004/37/EC	Long term exposure limit Respirable dust	0,1 mg/m ³
Additional advice:	Carcinogens or mutagens	

Additional advice: Longer and / or strong inhalation of alveolae

penetrating fine quartz dust can lead to pneumoconiosis, also know as silicosis. The effect of quartz dust (including cristobalite and tridymite) is a long-term effect and largely depends on the dose of dust, which is determined by the average dust concentration

determined by the average dust concentration over a long period of time (respirable fraction).

The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

To avoid dust formation, closed systems (e.g. silo with feed system), local extractors or other technical control devices should be used, e.g. plastering machines or continuous mixers with special auxiliary equipment for collecting dust.

Washing facilities / water for rinsing eyes and skin should be available. Maintain air concentrations below occupational exposure standards.

AGUAPLAST RAPID FASSADE

Individual protection measures, such as personal protective equipment

a) Eye/face protection

b) Skin protection Hand protection Safety glasses with side-shields conforming to EN166

Nitrile coated cotton gloves Break through time: 480 min Minimum thickness: 0.8 mm

Protective gloves complying with EN 388.

e.g. KCL 102 Sahara® Top (Kächele-Cama-Latex GmbH, Hotline:

0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Gloves to afford protection from chemicals (cat. III) are not

required.

Soaked gloves should be changed. Keep replacement gloves

available.

After washing hands, replenish lost skin oil by means of oily skin

ointment.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace

conditions (mechanical strain, duration of contact).

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one

producer to the other. Long sleeved clothing

Body Protection Long sleeved clothing c) Respiratory protection Avoid inhalation of particles.

Mixing and transferring dry mortars in open systems:

Compliance with the maximum permissible levels at the workplace is to be ensured by effective dust control measures, e.g. local extraction devices. Where this is not possible, particle-filtering half masks of type FFP2 (tested in accordance with EN 149) are to be

used.

Manual working of ready-to-use mortar: No respiratory protection

necessary.

Machining of mortar: No respiratory protection necessary.

Environmental exposure controls

General advice The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance powder
Colour white
Odour characteristic

AGUAPLAST RAPID FASSADE

Odour Threshold No data available

pH > 11,5 (20 °C)

Concentration: 10 % (aqueous suspension)

Melting point/freezing point Not applicable

Initial boiling point and boiling

range

not applicable

Flash point

not applicable

Evaporation rate not applicable

Flammability (solid, gas) The product is not flammable.

Upper explosion limit / Upper

flammability limit

not applicable

Lower explosion limit / Lower

flammability limit

not applicable

Vapour pressure No data available

Density ca. 2,424 g/cm³ (23 °C)

Solubility(ies)

Water solubility
Partition coefficient: n-

octanol/water

Not applicable

not determined

Auto-ignition temperature not auto-flammable

Decomposition temperature No data available

Viscosity

Viscosity, dynamic not applicable

Explosive properties Not explosive

Oxidizing properties Not applicable

9.2 Other information

Flow time not applicable

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

AGUAPLAST RAPID FASSADE

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

10.4 Conditions to avoid

Conditions to avoid Avoid exposure to water and moisture during storage

(moisture leads to an alkaline reaction which causes the

mixture to harden).

10.5 Incompatible materials

Materials to avoid Reacts exothermically with acids; the moist product is alkaline

and reacts with acids, ammonium salts and base metals, e.g.

aluminium, zinc, brass. The reaction with base metals

produces hydrogen.

10.6 Hazardous decomposition products

Hazardous No decomposition if stored and applied as directed.

decomposition products

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product:

Acute oral toxicity Based on available data, the classification criteria are not

met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not

met.

Skin corrosion/irritation

Product:

Causes skin irritation.

Components:

portland cement:

Causes skin irritation.

Serious eye damage/eye irritation

Product:

Causes serious eye damage.

Components:

portland cement:

Causes serious eye damage.

AGUAPLAST RAPID FASSADE

Respiratory or skin sensitisation

Product:

May cause an allergic skin reaction. Does not cause skin sensitisation.

Components:

portland cement:

May cause an allergic skin reaction.

Germ cell mutagenicity

Product:

Genotoxicity in vitro Based on available data, the classification criteria are not

met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Effects on fertility Based on available data, the classification criteria are not

met

Developmental Toxicity Based on available data, the classification criteria are not

met.

STOT - single exposure

Product:

Based on available data, the classification criteria are not met.

Components:

portland cement:

Exposure routes Inhalation

Assessment May cause respiratory irritation.

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Toxicology, Metabolism, Distribution

Further information

Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards Endocrine disrupting properties

Product:

AGUAPLAST RAPID FASSADE

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Experience with human exposure

Product:

General Information Cement may exacerbate existing illnesses of the skin, eyes

and respiratory passages, e.g. in case of pulmonary

emphysema or asthma.

Further information

Product:

Remarks : The product itself has not been tested. The mixture is

classified in accordance with Annex I to EC Directive

1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish No data available

12.2 Persistence and degradability

Product:

Biodegradability No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation No data available

12.4 Mobility in soil

Product:

Mobility Not applicable

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

AGUAPLAST RAPID FASSADE

Additional ecological information

Eco-toxic effects, in particular aquatic toxicity, are only possible when larger quantities are released into water

resulting in a change of the pH-value.

Do not flush into surface water or sanitary sewer system.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any

waste.

When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC). Opened and left-over materials can be used later. Only material no longer suitable for use should be mixed with water and allowed

to harden.

Hardened product residues may be disposed of as industrial waste or building rubble under waste codes 17 01 01 or 10 13 14. Unhardened product residues should be disposed of under the

recommended waste code number.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the

unused product.

Waste key for the unused

product

Empty packaging should be recycled through disposal systems. 17 09 03* other construction and demolition wastes (including

mixed wastes) containing hazardous substances

(*) hazardous waste in terms of the European directive

2008/98/EG

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

14.6 Special precautions for user

AGUAPLAST RAPID FASSADE

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations

Comply with the statutory regulations on health and safety at work. Take note of Dir 94/33/EC on the protection of young people at

work.

Take note of Dir 92/85/EEC on the safety and health at work of

pregnant workers.

The cement in the product is chromate-reduced. Persons with a

chromate allergy should not handle the product.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.

AGUAPLAST RAPID FASSADE

Full text of other abbreviations

Eye Dam. : Serious eye damage Skin Irrit. : Skin irritation : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x\% response: ELx - Loading rate associated with x\% response: EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information The assessment was carried out in accordance with Article 6

(5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your

understanding in this matter.

Department issuing MSDS Contact person European

Union

REG_EU / EN

beissier.laboratorio@beissier.es

AGUAPLAST RAPID FASSADE