

SAFETY DATA SHEET

AGUAPLAST TOP FILL

Ref.	130000007479/
Rev. no.	1.3
Revision Date	29.06.2023
Print Date	29.06.2023

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name AGUAPLAST TOP FILL

1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating material

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

Beissier S.A.U.
Txirrita Maleo, 14
20 100 Errentería (Guipúzcoa)
Phone: +34 943 344 070
Fax: +34 943 517 802

E-mail address of person responsible for the SDS European Union beissier.laboratorio@beissier.es

1.4 Emergency telephone number European Union

Phone: +44 (0) 1865 407333

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

AGUAPLAST TOP FILL

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

These are preservatives.
Avoid contact with the skin and the eyes.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47-XXXX	Repr. 2; H361d Aquatic Chronic 3; H412	≥ 0,25 - < 1
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Acute Tox. 2; H330 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1 ≥ 0,05 %	≥ 0,025 - < 0,05
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9 613-167-00-5	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1;	≥ 0,0002 - < 0,0015

AGUAPLAST TOP FILL

		<p>H410 Eye Dam. 1; H318 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit Skin Corr. 1C ≥ 0,6 % Skin Irrit. 2 0,06 - < 0,6 % Eye Irrit. 2 0,06 - < 0,6 % Skin Sens. 1A ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %</p>	
2-methyl-2H-isothiazol-3-one	2682-20-4 220-239-6	<p>Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 2; H330 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1</p> <hr/> <p>specific concentration limit Skin Sens. 1A ≥ 0,0015 %</p>	≥ 0,0002 - < 0,0015

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

General advice

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Never give anything by mouth to an unconscious person.
If unconscious, place in recovery position and seek medical

AGUAPLAST TOP FILL

Inhalation	advice. Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.
No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray

Unsuitable extinguishing media High volume water jet

5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:
Carbon monoxide
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Additional advice Wear self-contained breathing apparatus for firefighting if necessary.
Use water spray to cool unopened containers.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Do not breathe vapour.

6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and

AGUAPLAST TOP FILL

cleaning up	place in container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents. Dispose of contaminated material as waste according to item 13. Clean contaminated surface thoroughly.
6.4 Reference to other sections	Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling	Avoid contact with skin and eyes. Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions.
Advice on common storage	Protect from frost, heat and sunlight. Keep away from oxidizing agents and strongly acid or alkaline materials.

7.3 Specific end use(s)	For further information, see also Technical Data Sheet for the product.
--------------------------------	---

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

a) Eye/face protection	Wear protective goggles for protection against splashed liquid. Safety glasses with side-shields conforming to EN166
------------------------	---

AGUAPLAST TOP FILL

b) Skin protection
Hand protection

Recommended preventive skin protection
Before starting work, apply water-resistant skincare preparations to exposed skin areas.
Protective gloves should be worn in case of skin contact during preparation and application.

Break through time: 480 min
Minimum thickness: 0,11 mm
Gloves made of nitrile rubber, e.g. KCL 740 Dermatril® (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.
Cotton undergloves are recommendable when wearing protective gloves!
Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

Body Protection

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Work clothes
Skin should be washed after contact.

c) Respiratory protection

Do NOT use solvents or thinners.
No personal respiratory protective equipment normally required.
In case of insufficient ventilation, wear suitable respiratory equipment.
Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog.
Respiratory protection complying with EN 143.

Environmental exposure controls**General advice**

The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance	paste
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	ca. 8 - 9 (20 °C)
Melting point/freezing point	No data available
Initial boiling point and boiling range	No data available
Flash point	Not applicable

AGUAPLAST TOP FILL

Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	ca. 1,4 g/cm ³
Solubility(ies)	
Water solubility	Not applicable
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Viscosity	
Viscosity, dynamic	No data available
Viscosity, kinematic	No data available
Explosive properties	Not explosive
Oxidizing properties	Not applicable

9.2 Other information

Flow time	No data available
-----------	-------------------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

10.4 Conditions to avoid

Conditions to avoid Stable under recommended storage and handling conditions (see section 7).

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases
 Strong oxidizing agents

AGUAPLAST TOP FILL**10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

Components:**1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity LD50 (Rat): 532 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity LC50 (Rat): 0,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Assessment: Corrosive to the respiratory tract.
Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

2-methyl-2H-isothiazol-3-one:

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Assessment: Corrosive to the respiratory tract.
Toxic if inhaled.

Acute dermal toxicity Toxic in contact with skin.

Skin corrosion/irritation**Product:**

Based on available data, the classification criteria are not met.

Components:**1,2-benzisothiazol-3(2H)-one:**

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

AGUAPLAST TOP FILL

2-methyl-2H-isothiazol-3-one:
Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Product:
Based on available data, the classification criteria are not met.

Components:

1,2-benzisothiazol-3(2H)-one:
Causes serious eye damage.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):
Causes serious eye damage.

2-methyl-2H-isothiazol-3-one:
Causes serious eye damage.

Respiratory or skin sensitisation

Product:
Based on available data, the classification criteria are not met.

Components:

1,2-benzisothiazol-3(2H)-one:
May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):
May cause an allergic skin reaction.

2-methyl-2H-isothiazol-3-one:
May cause an allergic skin reaction.

Germ cell mutagenicity

Product:
Genotoxicity in vitro
Based on available data, the classification criteria are not met.

Carcinogenicity

Product:
Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:
Effects on fertility
Based on available data, the classification criteria are not met.

Developmental Toxicity
Based on available data, the classification criteria are not met.

Components:

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:
Developmental Toxicity
Suspected of damaging the unborn child.

STOT - single exposure

Product:
Based on available data, the classification criteria are not met.

AGUAPLAST TOP FILL

STOT - repeated exposure**Product:**

Based on available data, the classification criteria are not met.

Aspiration toxicity**Product:**

Based on available data, the classification criteria are not met.

Further information**Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex 1 to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information**Product:**

Remarks : The product itself has not been tested. The mixture is classified in accordance with Annex 1 to EC Directive 1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity****Product:**

Toxicity to fish No data available

Components:**1,2-benzisothiazol-3(2H)-one:**

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia (water flea)): 3,27 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0,04 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

AGUAPLAST TOP FILL

M-Factor (Acute aquatic toxicity)	1
Toxicity to fish (Chronic toxicity)	NOEC: 0,21 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 215
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 1,2 mg/l Exposure time: 21 d Species: Daphnia (water flea) Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	1
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia (water flea)): 0,12 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	100
Toxicity to fish (Chronic toxicity)	NOEC: 0,098 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,004 mg/l Exposure time: 21 d Species: Daphnia (water flea)
M-Factor (Chronic aquatic toxicity)	100
2-methyl-2H-isothiazol-3-one:	
Toxicity to fish	LC50 (Fish): 4,77 mg/l Exposure time: 96 h Test Type: flow-through test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	LC50 (Daphnia magna (Water flea)): 0,934 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	NOEC (Pseudokirchneriella subcapitata (algae)): 0,05 mg/l Exposure time: 120 h Test Type: static test

AGUAPLAST TOP FILL

EC50 (Pseudokirchneriella subcapitata (algae)): 0,138 mg/l
Exposure time: 120 h
Test Type: static test

M-Factor (Acute aquatic toxicity) 10

Toxicity to microorganisms EC50 (activated sludge): 41 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) NOEC: 2,38 mg/l
Exposure time: 98 d
Species: Oncorhynchus mykiss (rainbow trout)
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) NOEC: 0,044 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) 1

12.2 Persistence and degradability**Product:**

Biodegradability No data available

Components:**1,2-benzisothiazol-3(2H)-one:**

Biodegradability not rapidly degradable

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Biodegradability not rapidly degradable

2-methyl-2H-isothiazol-3-one:

Biodegradability Readily biodegradable.

12.3 Bioaccumulative potential**Product:**

Bioaccumulation No data available

Components:**1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-octanol/water log Pow: 0,7
Method: OECD Test Guideline 117

2-methyl-2H-isothiazol-3-one:

Bioaccumulation Bioconcentration factor (BCF): 3,16

12.4 Mobility in soil**Product:**

Mobility No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment This substance/mixture contains no components considered

AGUAPLAST TOP FILL

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Allow plaster residues to dry, or thicken with cementitious binders.
Contaminated packaging	Unhardened product residues should be disposed of under the recommended waste code number. Packaging that is not properly emptied must be disposed of as the unused product.
Waste key for the unused product	Empty packaging should be recycled through disposal systems. 08 01 12 Waste paint and varnish other than those covered by 08 01 11

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

AGUAPLAST TOP FILL

14.6 Special precautions for user

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC
Directive 2010/75/EU 2 %

VOC
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012
of the European Parliament
and the Council concerning the
export and import of dangerous
chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.

AGUAPLAST TOP FILL

H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H361d	: Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data

AGUAPLAST TOP FILL

Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS
Contact person European
Union
REG_EU / EN

beissier.laboratorio@beissier.es