

FIXACRYL SPRAY

Ref. 130000007542/

Rev. no. 1.3

Revision Date 17.10.2024 Print Date 07.05.2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name FIXACRYL SPRAY

Unique Formula Identifier (UFI) T4W2-S0EA-F00F-MFM7

1.2 Relevant identified uses of the substance or mixture

of the substance or mixture Coating and uses advised against Spraying

Uses advised against This information is not available.

1.3 Details of the supplier of

the safety data sheet

Beissier S.A.U. Txirrita Maleo, 14

20 100 Errentería (Guipúzcoa) Phone: +34 943 344 070 Fax: +34 943 517 802

E-mail address of person responsible for the SDS European Union

beissier.laboratorio@beissier.es

1.4 Emergency telephone number European Union

Phone: +44 (0) 1865 407333

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

FIXACRYL SPRAY

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements : P101 If medical advice is needed, have product container or label

at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe spray.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

Additional Labelling

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1). May produce an allergic reaction.

These are preservatives.

Avoid contact with the skin and the eyes.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
ethanol	64-17-5	Flam. Liq. 2; H225	≥ 20 - < 30
	200-578-6	Eye Irrit. 2; H319	
	603-002-00-5		
	01-2119457610-43-		
	XXXX		
triethylamine	121-44-8	Flam. Liq. 2; H225	≥ 0,05 - < 0,3
	204-469-4	Acute Tox. 3; H301	

FIXACRYL SPRAY

		612-004-00-5 01-2119475467-26- XXXX	Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1A; H314 Eye Dam. 1; H318 specific concentration limit STOT SE 3; H335 ≥ 1 % Acute toxicity estimate Acute oral toxicity: 100 mg/kg Acute inhalation toxicity: 7,2 mg/l Acute dermal toxicity: 300 mg/kg	
1,2-benzi	sothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60- XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A ≥ 0,036 %	< 0,05
isothiazoli 7]and 2-m	nass of: 5-chloro-2-methyl-4- in-3-one[EC no.247-500- nethyl-2H-isothiazol-3- o.220-239-6] (3:1)	55965-84-9 613-167-00-5 01-2120764691-48- XXXX	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C ≥ 0,6 % Skin Irrit. 2 0,06 - < 0,6 % Eye Irrit. 2	< 0,0015

FIXACRYL SPRAY

		0,06 - < 0,6 % Skin Sens. 1A ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %	
Substances with a workplace exposure	limit :		
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37- XXXX	Flam. Gas 1; H220 Press. GasH280	≥ 20 - < 30

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice When symptoms persist or in all cases of doubt seek medical advice.

Never give anything by mouth to an unconscious person.

If unconscious, place in recovery position and seek medical advice.

Inhalation Move to fresh air in case of accidental inhalation of vapours or

decomposition products. Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

If symptoms persist, call a physician.

Skin contact Take off contaminated clothing and shoes immediately.

Wash skin thoroughly with soap and water or use recognized skin

cleanser.

Do NOT use solvents or thinners.

If skin irritation persists, call a physician.

Eye contact In case of eye contact, remove contact lens and rinse immediately with

plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

Ingestion Rinse mouth with water.

If swallowed, seek medical advice immediately and show this container or

label.

Keep at rest.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media CO2, extinguishing powder or water spray. Fight larger fires with water

spray or alcohol resistantfoam. High volume water jet

Unsuitable extinguishing

media

5.2 Special hazards arising from the substance or

mixture

Fire may cause evolution of:

Carbon monoxide
Carbon dioxide (CO2)

Nitrogen oxides (NOx)

FIXACRYL SPRAY

Exposure to decomposition products may be a hazard to health.

Cool closed containers exposed to fire with water spray. In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.

Additional advice Fire residues and contaminated fire extinguishing water must be disposed

of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

5.3 Advice for firefighters

Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapour. Prevent unauthorized access.

6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the

soil. If the product contaminates rivers and lakes or drains inform respective

authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section

Clean with detergents. Avoid solvents. Clean contaminated surface thoroughly.

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other

sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Comply with the statutory regulations on health and safety at work. Advice on safe handling

Avoid formation of aerosol.

Prevent the creation of flammable or explosive concentrations of vapour

in air and avoid vapour concentration higher than the

occupational exposure limit values.

The product should only be used in areas from which all naked lights and

other sources of ignition have been excluded.

All metal parts of the mixing and processing equipment must be earthed. Operators should wear antistatic footwear and clothing. No sparking tools

should be used.

Do not breathe spray, vapour. Hygiene measures

Take off all contaminated clothing immediately. Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the product. After washing hands, replenish lost skin oil by means of oily skin

ointment.

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container.

Keep container tightly closed. Never use pressure to empty: container is

not a pressure vessel. Nosmoking. Prevent unauthorized access.

Containers which are opened must be carefully resealed and kept upright

to prevent leakage.

Keep in a well-ventilated place. Protect from frost, heat and sunlight.

Advice on protection against

Vapours are heavier than air and may spread along floors.

FIXACRYL SPRAY

fire and explosion Vapours may form explosive mixtures with air.

Keep away from sources of ignition - No smoking.

Take measures to prevent the build up of electrostatic charge. Avoid heating over 50 $^{\circ}\text{C}.$

Further information on storage

Advice on common storage

conditions

Keep away from combustible materials.

Keep away from food, drink and animal feedingstuffs.

Keep away from oxidizing agents and strongly acid or alkaline materials.

Storage temperature 5 - 50 °C

7.3 Specific end use(s) For further information, see also Technical Data Sheet for the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC	
			1.920 mg/m³		
	Further information: Indicative Further information: Contains no substances with occupational exposure limit va			•	
				ure limit values.	
triethylamine	121-44-8	TWA	2 ppm	2000/39/EC	
			8,4 mg/m³		
	Further information	ormation: Identifies the possibility of significant uptake through the skin			
		STEL	3 ppm	2000/39/EC	
			12,6 mg/m³		
	Further information	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this shoul beachieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Break through time : 60 min

Glove thickness : 0,7 mm

Monitoring procedures for the assessment of workplace exposure: standard EN 482

FIXACRYL SPRAY

Remarks : e.g. KCL 898 "Butoject®" - butyl rubber protective glove - (Kächele-

Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de)or

equal.

Dispose of wetted gloves at the end of the shift!

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should

under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one

producer to the other.

Skin and body protection : Preventive skin protection

Long sleeved clothing

Personal should wear antistatic clothings made of natural fiber or of

high temperature resistant synthetic fiber. All parts of the body

should be washed after contact.

Respiratory protection : When workers are facing concentrations above the occupational

exposure limit values they must use appropriate certified respirators.

Breathing protection equipment required in inadequately ventilated

places and during spraying.

In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

Combination filter A-P2

Respiratory protection complying with EN 14387.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : transparent

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

FIXACRYL SPRAY

Initial boiling point and boiling

range

No data available

Flammability : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : -41 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : Not applicable

Flow time : Not applicable

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-

octanol/water

: not determined

Vapour pressure : < 300 kPa (50 °C)

Density : ca. 0,836 g/cm³ (20 °C)

Relative vapour density : No data available

FIXACRYL SPRAY

9.2 Other information

Explosives : In use may form flammable/explosive vapour-air mixture.

Oxidizing properties : Not applicable

Self-ignition : >

240 °C

Evaporation rate : not applicable

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions Vapours may form explosive mixture with air.

Reacts with acids.

Reacts with oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid Direct sources of heat.

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity Based on available data, the classification criteria are not met.

FIXACRYL SPRAY

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components: triethylamine:

Acute oral toxicity Acute toxicity estimate: 100 mg/kg

Acute inhalation toxicity Acute toxicity estimate: 7,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity LD50 (Rat): 532 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity LC50 (Rat): 0,4 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Acute oral toxicity Toxic if swallowed.

Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

Skin corrosion/irritation

Product:

Based on available data, the classification criteria are not met.

Components:

triethylamine:

Causes severe skin burns and eye damage.

1,2-benzisothiazol-3(2H)-one:

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Product:

Based on available data, the classification criteria are not met.

Components:

ethanol:

Species Rabbit

Method OECD Test Guideline 405 Causes serious eye irritation.

triethylamine:

Causes serious eye damage.

1,2-benzisothiazol-3(2H)-one:

Causes serious eye damage.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

FIXACRYL SPRAY

Causes serious eye damage.

Respiratory or skin sensitisation

Product:

Based on available data, the classification criteria are not met.

Components:

1,2-benzisothiazol-3(2H)-one:

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

Germ cell mutagenicity

Product:

Genotoxicity in vitro Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Effects on fertility Based on available data, the classification criteria are not met.

Developmental Toxicity Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Toxicology, Metabolism, Distribution

Further information

Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2

and 3 for details).

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health

effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular

FIXACRYL SPRAY

weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

Further information

Product:

Remarks : The product itself has not been tested. The mixture is classified in

accordance with Annex I to EC Directive 1272/2008. (See sections 2

and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish No data available

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia (water flea)): 3,27 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 0,04 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) 1

Toxicity to fish (Chronic toxicity) NOEC: 0,21 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 215

Toxicity to daphnia and other aquatic invertebrates (Chronic

toxicity)

NOEC: 1,2 mg/l Exposure time: 21 d

Species: Daphnia (water flea) Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia (water flea)): 0,12 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic plants EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l

Exposure time: 48 h

NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l

FIXACRYL SPRAY

Exposure time: 48 h

NOEC: 0,004 mg/l

M-Factor (Acute aquatic toxicity) 100

Toxicity to fish (Chronic toxicity) NOEC: 0,098 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic

Exposure time: 21 d toxicity) Species: Daphnia (water flea)

M-Factor (Chronic aquatic 100

toxicity)

12.2 Persistence and degradability

Product: Biodegradability

No data available

Components:

1,2-benzisothiazol-3(2H)-one:

Biodegradability not rapidly degradable

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-

isothiazol-3-one[EC no.220-239-6] (3:1):

Biodegradability not rapidly degradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation No data available

Components:

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: nlog Pow: 0,7

octanol/water Method: OECD Test Guideline 117

dimethyl ether:

Partition coefficient: nlog Pow: 0,1

octanol/water 12.4 Mobility in soil

Product:

Mobility No data available

12.5 Results of PBT and vPvB assessment

Product:

This substance/mixture contains no components considered to be Assessment

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or

sewage systems.

FIXACRYL SPRAY

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any waste.

When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09

"Other Construction and Demolition Waste" Partial and residual quantities can be reused.

Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the

unused product.

Empty packaging should be recycled through disposal systems.

Waste key for the unused 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(*) hazardous waste in terms of the European directive 2008/98/EG

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

product

ADR 1950

IMDG 1950

IATA 1950

14.2 UN proper shipping name

ADR AEROSOLS

IMDG AEROSOLS

IATA Aerosols, flammable

14.3 Transport hazard class(es)

ADR 2.1

IMDG 2.1

IATA 2.1

14.4 Packing group

ADR

Packing group Not Assigned

Classification Code 5F

Labels 2.1

Tunnel restriction code (D)

IMDG

Labels 2.1

EmS number F-D, S-U

IATA

FIXACRYL SPRAY

Labels 2.1

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Additional advice

ADR: Up to 1 I per inner package, transport as limited quantity in

accordance with ADR 3.4.

IMDG IMDG: Up to 1 I per inner package, transport as limited quantity in

accordance with IMDG Code 3.4.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

Directive 2010/75/EU 55,34 %

VOC

Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals REACH - Restrictions on the manufacture, placing on the

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Not applicable

Conditions of restriction for the following entries should be considered: (75)triethylamine

Other regulations Comply with the statutory regulations on health and safety at work.

Take note of Dir 94/33/EC on the protection of young people at work. Take note of Dir 92/85/EEC on the safety and health at work of pregnant

workers.

15.2 Chemical safety assessment

FIXACRYL SPRAY

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H310	:	Fatal in contact with skin.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H331	:	Toxic if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Eye Irrit. : Eye irritation Flam. Gas Flammable gases Flam. Liq. Flammable liquids Press. Gas Gases under pressure Skin Corr. Skin corrosion Skin Irrit. Skin irritation Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC -Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw -Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

FIXACRYL SPRAY

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information The assessment was carried out in accordance with Article 6 (5) and

Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS Contact person European Union REG_EU / EN

beissier.laboratorio@beissier.es

FIXACRYL SPRAY