

AGUAPLAST ALL 4 IN

All-round ready mixed filler for interior application



GENERAL CHARACTERISTICS

USAGES

- Renovating on most interior painted substrates.
- Levelling of rough surfaces.
- Skim coating: Ensures a fine and low absorbent surface.
- Plasterboards: Joint filling and finishing, allowing plasterboard finish to any surface quality level.

CHARACTERISTICS

- Can be applied in thick coats up to 6 mm.
- Smooth application and easy sanding.
- Can be applied by trowel/blade, roller, airless machines and bazooka taping and finishing equipments.
- Very fine and white finish.
- Can be overcoated with any kind of paint.

SUITABILITY RATING ACCORDING TO THE SUBSTRATE

From 1 being suitable to 3 being highly suitable

SUBSTRATES	Suitability
Interior - Absorbent	
Concrete, cement and lime mortars	3
Cellular concrete, concrete blocks, sand-lime blocks	3
Ceramic bricks	3
Plasterboard, gypsum fiber board, gypsum block	3
Plaster and gypsum	3
Cement and fiber-cement boards	3
Matt Paints	3
Natural stone, stone cladding	2
Wood, timber, plywood, chipboard	2
Interior - Non absorbent	
Old coats of satin/gloss/egg shell paints	After sanding
Old coats of oil-based, solvent-based paints	After sanding
Sprinkle effect, decorative acrylic coatings	3
Fiberglass wall coverings, painted or not	3
Ceramic tiles, glass mosaic, glazing substrates	-
Smooth concrete	2

TECHNICAL DATA

Product	
Form	Paste
Composition	Water, fillers, binders, additives, etc.
Color	White
Particle size	< 100 µm
Density	1.75 g/cm ³
Application	
Temperature	5-35 °C
Tools	Trowel, blade, spatula, airless equipment, bazooka taping machines
Application thickness	6 mm
Working time	No limit
Drying time (23°C - 65% HR)	24 h/mm
Consumption	1.75 kg/m ² /mm
Sanding/Overcoating time	After completed drying
Interior/Exterior	Interior

PACKING

Product Code	Packaging	Units/Carton	Palletization
70530-003	Bucket 6 kg	2	144 Buckets
70530-002	Bucket 15 kg	-	44 Buckets
70530-001	Bucket 25 kg	-	33 Buckets

PREPARATION AND APPLICATION

SUBSTRATE PREPARATION

Apply on dry substrates. The substrate must be cohesive, load-bearing and clean of dust, grease, wax or any other substance hindering a proper adhesion of the filler. Remove loose or poorly bonded parts of plaster, mortars, old coats of paints, etc. Apply DELTAFIX or other consolidating primer to harden feeble and chalky substrates. If necessary, treat absorbent substrates with FIXACRYL or another stabilizing primer to reduce surface absorption. All areas contaminated with mold and/or algae must be thoroughly cleaned, then treated with FUNGISTOP or another anti-fungal agent. Protect metallic parts with BEISSIER CHAMELEON or another anti-corrosion primer. Fill deep holes and larger gaps with AGUAPLAST UNIVERSAL PRO / EXPRESS. Repair and seal dynamic cracks with AGUAPLAST FIBRA or FLEX FILL.

In general, substrates must be treated and prepared according to local standards. If any doubt, it is highly recommended to perform a test application on a small area to determine suitability, compatibility and application conditions.

APPLICATION

Ready to use paste. Apply manually using stainless steel trowel, spatula or blade. Can be sprayed with Airless machine (minimum delivery volume 5 l/min - nozzle up to 5.31). Neither strainer nor filter needed for application. Follow machine manufacturers' instructions for cleaning. Clean tools with water immediately after use. When working in interiors, allow air ventilation to ensure a correct drying process. Can be overcoated with any kind of paint, finishing coating, wallpaper, etc. Decorative finishes can be applied once the surface is dry.

CAUTIONS, STORAGE, HEALTH AND SAFETY

CAUTIONS

Do not apply at temperatures below 5°C or above 35 °C.
Do not apply on substrates subjected to constant humidity.
Do not apply on glazed surfaces (tiles, mosaic, etc.).

STORAGE AND SHELF LIFE.

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 1 year. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number YDDD##. Example: Batch Nr. 314401 = 2023 May 24 (144/365). Close properly after use. Open packages should be consumed within the soonest possible.

HEALTH AND SAFETY

Consult the latest Safety Data Sheet available at www.beissier.com. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear gloves and goggles. Avoid inhalation of particles when sanding. Keep out of reach of children.

DISPOSAL PROCEDURES

Dispose of waste and residues in accordance with local authority requirements. Paste must not be thrown away into drains. If recycling is not practicable, dispose of in compliance with local regulations.

Sustainable packaging

Recycled & 100% recyclable packaging.



REGULATIONS AND CERTIFICATIONS

Applicable Norms and Certificates:

Classification EN 16566:2014 (G3S2V0W0A0C0R0)
Classification EN-13963:2005

	19 B.0088 EN 13963:2005	AGUAPLAST ALL 4 IN Joint compound for laminated gypsum board joints. Type A3.
		Reaction to fire – A2 s1 d0

Environmental Certifications:



Note: The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.