

# AGUAPLAST RENOVA JOINT

Tile grout



## GENERAL CHARACTERISTICS

### USAGES

- Renovating and refreshing old tile joints.
- Ideal for kitchens and bathrooms.
- Interior and exterior use.

### CHARACTERISTICS

- Deep white finish.
- Water, humidity & mould resistant.
- Excellent adhesion to all kind of substrates.

### SUITABILITY RATING ACCORDING TO THE SUBSTRATE

From 1 being suitable to 3 being highly suitable

SUBSTRATES	Suitability
<b>Interior - Absorbent</b>	
Concrete, cement and lime mortars	-
Cellular concrete, concrete blocks, sand-lime blocks	-
Ceramic bricks	-
Plasterboard, gypsum fiber board, gypsum block	-
Plaster and gypsum	-
Cement and fiber-cement boards	-
Matt Paints	-
Natural stone, stone cladding	-
Wood, timber, plywood, chipboard	-
<b>Interior - Non absorbent</b>	
Old coats of satin/gloss/egg shell paints	-
Old coats of oil-based, solvent-based paints	-
Sprinkle effect, decorative acrylic coatings	-
Fiberglass wall coverings, painted or not	-
Ceramic tiles, glass mosaic, glazing substrates	3
Smooth concrete	-

### TECHNICAL DATA

Product	
Form	Paste
Composition	Water, fillers, binders, additives, etc.
Color	White
Particle size	< 200 µm
Density	1.6 g/cm <sup>3</sup>

Application	
Temperature	5-35 °C
Tools	Rubber spatula, finger, sponge
Application thickness	3 mm
Working time	No limit
Drying time (23°C - 65% HR)	24 h
Consumption	1 tube refreshes approx. 1 M2 of 10x10cm sized tiles
Sanding/Overcoating time	24 h
Interior/Exterior	Interior/Exterior

### PACKING

Product Code	Packaging	Units/Carton	Palletization
70477-001	Tube 200 ml	12	100 Cartons

## PREPARATION AND APPLICATION

### SUBSTRATE PREPARATION

Apply on dry substrates. The substrate must be cohesive, load-bearing and clean of dust, grease, wax or any other substance hindering a proper adhesion of the filler. All areas contaminated with mold and/or algae must be thoroughly cleaned, then treated with FUNGISTOP or another anti-fungal agent.

In general, substrates must be treated and prepared according to local standards. If any doubt, it is highly recommended to perform a test application on a small area to determine suitability, compatibility and application conditions.

### APPLICATION

Massage the tube before use. Ready to use paste. Fill the joint and smooth with a round ended spatula. Wait 30 minutes before removing excess with damp cloth. Clean tools with water immediately after use. When working in interiors, allow air ventilation to ensure a correct drying process. Can be overcoated with any kind of paint.

## CAUTIONS, STORAGE, HEALTH AND SAFETY

### CAUTIONS

Do not apply at temperatures below 5°C or above 35 °C.  
Do not apply to tiles submerged under water (swimming pools, bath tub, etc.)

### STORAGE AND SHELF LIFE.

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 2 year. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number YDDD##. Example: Batch Nr. 314401 = 2023 May 24 (144/365). Close properly after use. Expel the air out from the tube and close cap tightly to prevent product from drying.

### HEALTH AND SAFETY

Consult the latest Safety Data Sheet available at [www.beissier.com](http://www.beissier.com). Keep out of reach of children.

### DISPOSAL PROCEDURES

Dispose of waste and residues in accordance with local authority requirements. Paste must not be thrown away into drains. If recycling is not practicable, dispose of in compliance with local regulations.

### Sustainable packaging

Recycled & 100% recyclable packaging.



## REGULATIONS AND CERTIFICATIONS

### Environmental Certifications:



**Note:** The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.