

# DRY WALL PRIMER

Water-based white primer ideal for plasterboard and new plaster



## GENERAL CHARACTERISTICS

### USAGES

- Regulates surface porosity across multiple substrates: Plasterboard, plaster, concrete, cement, concrete blocks, bricks, old painted substrates, etc.
- Ideal background and preparation for paintwork on any kind of substrate.
- Interior use.

### CHARACTERISTICS

- Improves adhesion of paints and other wall coverings.
- Excellent opacifying properties.
- Seals substrate porosity and reduces absorption.
- Improves performance of interior paints.
- Excellent consistency for smooth spread and easy application.
- Will produce no roller mark or stroke.
- Quick drying and overcoating.
- White matt finish.

### PACKING

Product Code	Packaging	Units/Carton	Palletization
70652-002	Bucket 4L	2	72
70652-001	Bucket 15L	-	33

### TECHNICAL DATA

Product	
Composition	Synthetic resins
Color	White
Appearance	Matt Finish
Density	1,60 g/cc
Application	
Temperature	5-35 °C
Tools	Brush, Roll or Spray Gun
Dilution	Brush / Roll: water max. 10% Spray Gun: water max. 10-20%
Drying time	1 h (touch dry)
Overpainting	After completed drying
Yield	Brush or Roll: 10-12 m <sup>2</sup> /L and coat. Spray Gun: 6-8 m <sup>2</sup> /L
Interior/Exterior	Interior

## PREPARATION AND APPLICATION

### SUBSTRATE PREPARATION AND APPLICATION

Apply on clean, dry and sound substrates. Make sure new plaster is completely dry before application.

Remove loose material and all traces of rust, calamine, grease or wax from substrate.

Do not apply at temperatures of below +5°C or above +35°C.

If necessary, stir to homogenize content before use. May be diluted with water up to 10% maximum.

Apply with paint roller or brush. Can be applied with painting machines.

Clean tools with water immediately after use.

## CAUTIONS, STORAGE, HEALTH AND SAFETY

### CAUTIONS

Substrate temperature: from 5°C to 35°C.

Application temperature: from 5°C to 35°C.

### STORAGE AND SHELF LIFE.

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 2 year. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number YDDD##. Example: Batch Nr. 314401 = 2023 May 24 (144/365). Close properly after use. Open packages should be consumed within the soonest possible.

### HEALTH AND SAFETY

Consult the latest Safety Data Sheet available at [www.beissier.com](http://www.beissier.com). Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear gloves and goggles.

### Sustainability recommendations

Used paint residues and packaging must not be disposed of with household waste, but rather in the places and containers provided for this purpose by the local authorities, whose waste disposal regulations must be complied with. Do not pour leftover paint down the sink or toilet. Minimise paint waste by calculating the amount of paint you will need. Recover unused paint for reuse. The reuse of paint should effectively minimise environmental impacts on the product life cycle.

### Sustainable packaging

Recycled & 100% recyclable packaging.



## REGULATIONS AND CERTIFICATIONS

### Environmental Certifications:



**Note:** The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.