

# FIXACRYL

Water based Priming & Sealing Spray



## GENERAL CHARACTERISTICS

### USAGES

- Seals absorbent backgrounds and hardens chalky, loose and feeble substrates.
- On cement, concrete, gypsum, plaster, lime mortars, old coats of paints, etc.
- Improves adhesion of paints and wall coverings.
- Interior and Exterior.

### CHARACTERISTICS

- Water based.
- Easy and quick application, ideal for local application and for small areas.
- Seals and stabilizes absorbent substrates.
- Reduces absorption of paints, improving scrubbing resistance of the same.
- Water proof and water vapor breathable.
- Colorless.

### TECHNICAL DATA

<b>Product</b>	
<b>Propellent</b>	DME
<b>Color</b>	Colorless
<b>Application</b>	
<b>Temperature</b>	5-35 °C (humidity < 70%)
<b>Cleaning of tools</b>	With water
<b>Consumption</b>	Approx. 12 M2 / 400 ML spray can
<b>Drying time</b>	Touch dry after 30 minutes at 23° C
<b>Overpainting</b>	After 24 hours depending on temperature and application conditions

### PACKING

Product Code	Packaging	Color	Units/ Carton	Palletization
70237-008	Spray 400ml	Colorless	6	116 cartons

## PREPARATION AND APPLICATION

### SUBSTRATE PREPARATION AND APPLICATION

Apply on clean, dry and sound substrates. Remove loose material and all traces of rust, calamine, grease or wax from substrate.

Shake well before use, at least 60 seconds until mixing balls are heard loose.

Apply at a distance of 20 - 25 cm from the substrate.

**CAUTIONS, STORAGE, HEALTH AND SAFETY****CAUTIONS**

Substrate temperature: from 5°C to 35°C.

Application temperature: from 5°C to 35°C.

Extremely flammable aerosol. Pressurised container: May burst if heated.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not breathe spray. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**STORAGE AND SHELF LIFE.**

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 2 year. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number. Explanation:

Figure 1 = last digit of the year, figures 2/3 = elapsed week of the year.

Example: Lot 6260016763. Storage life: until week 26 of the year 2026.

Open packages should be consumed within the soonest possible.

**HEALTH AND SAFETY**

Consult the latest Safety Data Sheet available at [www.beissier.com](http://www.beissier.com). Avoid direct contact with skin and eyes.

Keep out of reach of children.

**Sustainability recommendations**

Used residues and packaging must not be disposed of with household waste, but rather in the places and containers provided for this purpose by the local authorities, whose waste disposal regulations must be complied with.

**Note:** The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.